

| 12x14-LT Lean To Shed Materials - Build Your Own Backyard Shed iCreatables.com | | | |
|---|---|-----------------------|-------------|
| EXTERIOR MATERIALS | | | |
| CODE | DESCRIPTION | LENGTH / SIZE | QTY. |
| W7 | T1-11 Siding | 4'x8'x 1/2" | 12 |
| T4 | 1x4 Trim | 3 1/4" x 10' | 11 |
| R5 | Metal Drip Edge, install under roofing | 1 1/2" x 1 1/2" x 10' | 6 |
| R5.1 | Metal Drip Edge, install on top of roofing | 4" x 4" x 14' | 1 |
| R6 | Grace Ice and Water Shield | | 1 roll |
| R7 | 36" wide PBR metal roofing | 36" x 13'-5" | 5 |
| R11 | Corrugated roofing closure strip | 30 lineal feet | 1 |
| W10 | "Z" Metal flashing | 10' | 4 |
| FOUNDATION MATERIALS | | | |
| CODE | DESCRIPTION | LENGTH / SIZE | QTY. |
| F3 | 6x6 Skid, treated | 14'-0" | 3 |
| F5 | Gravel | | |
| FLOOR FRAMING MATERIALS | | | |
| CODE | DESCRIPTION | LENGTH / SIZE | QTY. |
| F1 | 2x6 Floor Joist | 12' | 12 |
| F2 | 2x6 Rim Joist | 16'-0" | 2 |
| F4 | O.S.B. T.&G. | 4'x8'x 3/4" | 6 |
| F10 | SIMPSON A23 CLIP | | 12 |
| WALL FRAMING MATERIALS | | | |
| CODE | DESCRIPTION | LENGTH / SIZE | QTY. |
| W1 | 2x4 Lumber | 8'-0" | 36 |
| W1.5 | 2x4 Lumber | 10'-0" | 12 |
| W2 | 2x4 Wall Plate, short | 12'-0" | 8 |
| W3 | 2x4 Wall Plate, long | 14'-0" | 6 |
| W5 | Door Trimmer | 8'-0" | 2 |
| W6 | 2x6 Header | 8'-0" | 2 |
| W7 | 4ft. x 8ft. Textured Plywood Siding, See exterior materials | | |
| ROOF FRAMING MATERIALS | | | |
| CODE | DESCRIPTION | LENGTH / SIZE | QTY. |
| R1 | 2x8 Rafter | 14'-0" | 12 |
| R2 | O.S.B. roof sheeting | 4'x8'x 7/16" | 11 |
| R4 | 2x8 Sub Facia | 16'-0" | 2 |
| R12 | 2X8 Blocking | 16'-0" | 2 |
| R15 | Simpson H2.5 Hurricane Tie | | 16 |
| DOORS | | | |
| D1 | See door plans for materials or purchase pre-hung doors | | |
| D1 | 6068 Pre-Hung Door, per owner | 6'-0" x 6'-8" | 1 |
| | Verify jamb size and rough opening for pre hung doors | | |
| FASTENERS (see door plans for door fasteners) | | | |
| 2 1/2" | 8d Coated Sinker-Roof Sheet, Joist/Rafter to Wall | | 5 lbs |
| 3 1/4" | 12d Coated Sinker-Floor Joist, Wall Frame | | 6 lbs. |
| 2 1/2" | 8d Galvanized-Siding | | 9 lbs. |
| | Metal Roof 1/4" hex head screw with neoprene bonded washer | | 3 lbs. |
| | Optional Asphalt Roof 1 1/4" long, 12 gauge, 3/8" head Roofing Nail | | 4 lbs. |
| | Optional Trim Screws #9 flat head, polymer 2.5" | | |
| | Construction Adhesive | 10 oz. | 3 |